



# DECLARATION OF PERFORMANCE

According to Regulation (EU) No.305/2011  
No. GGCB0XX/9

**ANTI-KOROZIN BB**



DECLARATION OF PERFORMANCE

1. Unique identification code of the product:  
**GGCB0XX**
2. Intended use/uses:  
**According to EN 1504-2:ZA.1d and EN 1504-2:ZA.1e, anti-carbonation coating for surface protection of concrete against ingress and moisture control.**  
**This product is intended for:**
  - **Ingress protection – Method 1.3 according to EN 1504-2 (Method 1.3 according to EN 1504-9)**
  - **Moisture control – Method 2.2 according to EN 1504-2 (Method 2.3 according to EN 1504-9)**
  - **Increasing resistivity by limiting moisture content – Method 8.2 according to EN 1504-2 (Method 8.3 according to EN 1504-9)**
3. Manufacturer:  
**ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia**
4. Authorised representative:  
**/**
5. System or systems of AVCP:  
**System 2+**
- 6a. Harmonised standard:  
**EN 1504-2:2004**

Notified body:

**Building Research Institute (N I S I) Ltd, 1618 Sofia, Bulgaria, №86 Nikola Petkov Blvd - notified body for construction products, with identification number NB 2032 in European Commission register performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued [Certificate of conformity of the factory production control](#).**



## 7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
Permeability to water vapour	<b>Class I, <math>S_D &lt; 5 \text{ m}</math></b>	<b>MKC EN 1504-2:2006</b>	<b>EN 1504-2:2004</b>
Capillary absorption and permeability to water	<b><math>w &lt; 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}</math></b>		
Adhesion after thermal compatibility: Freeze-thaw cycling with de-icing salt immersion	<b>Adhesion after 50 freeze-thaw cycles <math>\geq 1,5 \text{ N/mm}^2</math></b>		
Adhesion strength by pull-off test	<b><math>\geq 1,5 \text{ N/mm}^2</math></b>		
Permeability to $\text{CO}_2$	<b><math>S_D &gt; 50 \text{ m}</math></b>		
Reaction to fire	<b>Class B – s1, d0</b>		
Dangerous substances	<b>No performance determined</b>		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

DECLARATION OF PERFORMANCE

Signed for and on behalf of the manufacturer by:  
General Manager,



Zoran Petrovski, arch.eng.


Skopje, 07.02.2024



# CE MARKING

Annex to DoP No.GGCB0XX/9

DECLARATION OF PERFORMANCE

 2032	
ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia 13 GGCB0XX/9 EN 1504-2:2004 <b>ANTIKOROZIN BB</b> Anti-carbonation coating for surface protection of concrete against ingress and moisture control	
Permeability to water vapour	<b>Class I, <math>S_D &lt; 5 \text{ m}</math></b>
Capillary absorption and permeability to water	<b><math>w &lt; 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}</math></b>
Adhesion after thermal compatibility: Freeze-thaw cycling with de-icing salt immersion	<b>Adhesion after 50 freeze-thaw cycles <math>\geq 1,5 \text{ N/mm}^2</math></b>
Adhesion strength by pull-off test	<b><math>\geq 1,5 \text{ N/mm}^2</math></b>
Permeability to $\text{CO}_2$	<b><math>S_D &gt; 50\text{m}</math></b>
Reaction to fire	<b>Class B – s1, d0</b>
Dangerous substances	<b>No performance determined</b>

#### ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

#### NOTE

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.